



NOTE:

- ☆ When ordering always state height first.
- ☆ All configurations are viewed from the outside looking inside.
- ☆ The availability of certain sizes and configurations are dependent on the design wind load requirement. Confirm availability with your Westal Representative.
- ☆ It is recommended that a Westal Representative be consulted to determine the configuration best suited to individual requirements and sites.
- ☆ Other configurations are available upon request however should a service leaf be required to act as a main entrance, it is recommended that an uneven leaf configuration (ie. 3, 5, 7, etc) be used
- ☆ Maximum door leaf dimensions: 3000mm (high) or 900mm (wide) **and not to** exceed 40kg/leaf. A minimum sash width of 650mm applies.
- ☆ Dotted lines in above illustrations indicate service leaf.
- ☆ The elevations detail the first opening configuration shown in plan.
- ☆ The above opening configurations represent the possible openings for the specific number of leaves illustrated and **do not** indicate all the opening configurations possible within the single door unit.
- ☆ Standard hardware: self latching lever handle with deadlock (in satin chrome) to service leaf and lever operated, two point bolting system (keyed option available upon request) (in black) to other leaves as required.
- ☆ **As this product is top hung, a structurally supportive head is required. (to be supplied by builder)**
- ☆ Drawings may not be to scale.
- ☆ Available upon request (additional charges apply); - Energy efficient upgrades
- ☆ For wind & water resistance purpose all units open out from inside.
- ☆ Fly screen system for these units not available from Westal Windows.

E AND OE

WESTAL STANDARD PRODUCTS BOOK JULY 2010.xls LWC20/01/2011